

# SVMxxED Series



## Dimensions

## Product Summary

- 4 / 8ch Full HD Analogue real-time recording
- TVI / AHD / 960H supported by automatic detection (1080p/720p/960H/D1)
- H.264 half real-time 1080p recording & Playback(60fps for 4ch)
- Dynamic Push Notification to Ios and Android
- Panorama search
- Integrated GUI for search, copy and playback
- Direct AVI formatting for copy & Multiple channel backup as generic file format with embedded player
- Multiple GUI resolution adjustable to various monitor type ( HDMI, VGA)
- Low transmission latency
- 2-way full duplex audio
- Auto port forwarding (uPNP), DDNS
- Easy mobile connection (P2P)
- Configurable resolution, quality & fps for network streaming directly from client
- H264 based mobile device support : iOS / Android

## Major Specifications

\* OSD Menu is subject to change without prior notice

MODEL Name		SVM04ED	SVM08ED
Description		H264 Hybrid DVR	
Video	Number of Channels	4	8
	Camera	NTSC / PAL	
	Main Monitor	HDMI and VGA (1920x1080)	
	Sub Monitor	CVBS(BNC)	CVBS(BNC)
Audio	input/output	4 / 1	
	Audio codec	G.711	
Alarm	Sensor input	Not Supported	
	Alarm output	Not Supported	
Data	RS-485	1	
REC	1280x720	25/30fps/ch	
	960x480	25/30fps/ch	
	720x480	25/30fps/ch	
Playback	1920x1080	60/50fps	120/100fps
	search	Date/Time, Event, Archive, Log	
	Multi -Decoding	1, 4	1, 4, 9
Backup	Media	USB drive, External HDD, Network	
	Format	BMP, AVI, Raw data format	
Storage	HDD	Capacity of 1 HDD	6TB
		Internal HDDs	1
		e-SATA	n/a
User I/F	Input mode	External Keyboard controller, Mouse & HTTP API I/F, Front Key	
DDNS	Dynamic DNS	Yes (Free DDNS)	
Features		H264 with resolution size/quality/FPS control from various viewer.	
		Advanced video Detection Event ( Tampering, lens blocking, Defocus)	
		Event notification (motion, video loss, HDD S.M.A.R.T) Recording Status	
		Privacy zone masking, Covert, System Log	
Network	port	10/100M	10/100M
	protocol	DHCP,DDNS,P2P,UPNP,HTTP,NTP,SNMP,SMTP	
	No. of client	Push notification( IOS/Android)	
Dimension	(W x D x H) mm	254x220x43	254x220x43
Weight	kg	1.2	1.2
Power		DC 12V/2A	DC 12V/2A
Temperature	operation	5°C ~ 40°C/ 20~80% RH	