

SVR-5032NHI5**Product Summary**

- Video Input Resolution Max, 4K
- Recording Speed 7.5fps/ch (4K), 30fps/ch (2MP)
- Interface PTZ RS485 - Terminal Block
- Network Interface 2 x Ethernet 10/100/1G
- Network Compression H.265
- ONVIF Profile S

Major Specifications

| Model Name | | SVR-5032NHI5 |
|------------|--------------------|---|
| Video | Input | 32 IP |
| | Input Resolution | Max, 4K |
| | Output | 1 HDMI |
| | Output Resolution | Max. 4K |
| Recording | Speed | 7.5fps/ch (4K), 30fps/ch (2MP) |
| | Resolution | Max. 4K |
| | Compression | H.265, H.264, JPEG |
| Audio | Input | 1CH |
| | Output | 1CH |
| Interface | Senser In / Out | 4 IN / 1 OUT |
| | USB | 3 Port(Front 2, Rear1) |
| | PTZ | RS485 - Terminal Block |
| Network | Interface | 2 x Ethernet 10/100/1G |
| | Compression | H.265 |
| | Speed | 7.5fps(4MP) |
| | Resolution | Max. 4MP |
| System | OS | Embedded Linux 4.2 (Built-in Flash Memory) |
| | Pre / Post-Alarm | 5sec / 5sec~5min |
| | Recording Mode | Continuous, Event, Schedule |
| | Data Search | Calendar, Multi Day / Time, Event, Go to Time |
| | Backup Interface | USB, Network |
| | Backup Type | Video(RMS, AVI), Capture(JPEG), Log List, Setup Data |
| | Alarm Action | Buzzer, PTZ Preset, E-mail, Event Popup, Push |
| | User | 15 Users (Admin, User1 ~ User14) |
| | Network Viewer | NETUS-Pro, NETUS-Lite (Windows, Mac), NETUS-Eyes (iOS, Android) |
| Storage | ONVIF | ONVIF Profile S |
| | Primary / External | 4HDD |
| General | Size | 440 x 88 x 430 mm |
| | Weight(w/o HDD) | 8Kg |
| | Temp / Humidity | 5 ~ 40 °C / 10% ~ 80% |
| | PoE | Not Supported |
| | Power Supply | AC 100 ~ 250V, 50/60 Hz |
| | Power Consumption | 180W |