

# SVR-7016SHB



## Product Summary

- EX-SDI, HD\_SDI, TVI, CVI, 960H, IP 7brid DVR
- RTSP dual recording
- P2P Service
- Transcoding Playback
- Push Notification
- Dual LAN Port
- UHD display & FHD Spot
- Two way audio

## Major Specifications

Model Name		SVR-7016SHB
Video	Input	16 BNC
	Input Resolution	8MP, 4MP, 3MP, 2MP, 960H
	Output	1 HDMI , 1 VGA , 2 BNC ( 1 HD , 1 SD)
	Output Resolution	4K, FHD, SXGA, XGA
Recording	Speed	15fps/ch(4MP), 30fps/ch(2MP)
	Resolution	8MP, 4MP, 3MP, 2MP, 960H
Audio	Input	4RCA
	Output	1 HDMI, 1 RCA
Interface	Senser In / Out	16 / 4 - NC / NO
	USB	2 x USB 2.0
	PTZ / Keyboard	2 x RS485 - Terminal Block
	ATM / POS	Ethernet POS
Network	Interface	2 x Ethernet 10/100/1G
	Compression	H.264. JPEG
	Speed	10fps(4MP), 20fps(2MP)
	Resolution	Max. 4MP
Storage	Primary / Enternal	6 HDD, 2 eSATA
System	OS	Embedded Linux (Built-in Flash Memory)
	Pre / Post-Alarm	5sec /5sec~5min
	Recording Mode	Continuous, Event, Schedule
	Data Search	Smart, Panorama, Calendar, Multi Day / Time, Event, Go to Time
	Backup Interface	USB, Network
	Backup Type	Video(RMS, AVI), Capture(JPEG), Log List, Setup Data
	Alarm Action	Buzzer, PIZ Preset, E-mail, Relay, Spot, Event Popup, Callback, FTP, Push
	User	15 Users (Admin, User1 ~ User14)
	Network Viewer	Netus, VMS, Web Viewer, Mac Viewer, SmartEyes_Pro(iOS, Android)
	ONVIF	ONVIF Profile S
General	Size	440 x 88 x 430 mm
	Weight(w/o HDD)	8kg
	Temp / Humidity	5 ~ 40°C /10% ~80%
	Power Supply	AC 100~250V,50/60 Hz
	Power Consumption	80 Watts